



Tech Data Sheet

Superwash Fabric Cleaner



Description

The Superwash fabric cleaner is an alcohol-based cleaner used to clean the fabric, metal, composite, and fiberglass surfaces before applying primer and paint.



Components

- Superwash Fabric Cleaner



Suitable Substrates

- Fabric
- Metal
- Fiberglass
- Composite



Application

Application Density: Wet

Flash: 1-2 minutes

Application Conditions: *Minimum Temp* none

Max Temp none

Ambient Humidity none



Equipment Recommendations

- Clean terry cloth towel or rag



Physical Data

| | |
|------------------------|-----------------------------|
| Appearance & Odor | Colorless liquid; alcoholic |
| Vapor Density | Heavier than Air |
| Evaporation Rate | Slower than Ether |
| Boiling Point or Range | 177° F |
| Flashpoint | 55° F |



Safety

Before using any Superflite product be sure to read all MSDS, application instructions, and warnings. Always wear a properly fitted air purifying respirator with organic cartridges and a particulate filter or a fresh air supplied respirator (depending on product selection), eye protection, gloves, and protective clothing while exposed to any chemical.



Warning Statement

This product is intended for use by trained professionals only. Use as directed. The data presented herein was determined under our controlled conditions. Since environmental conditions play a large role in performance, variations in the data presented herein may be observed as environmental conditions change. This document does not constitute a warranty or guarantee of any kind. Use at your own risk.